



Type	Length	1.6 MPa				2.5 MPa				150LB				300LB				High			
		DN	NPS	L	L1	D	D1	D2	Z-ød	D	D1	D2	Z-ød	D	D1	D2	Z-ød	D	D1	D2	Z-ød
50	2"	108	43	165	125	102	4-ø18	165	125	102	4-ø18	150	120.7	92	4-ø19	165	127	92	8-ø19	130	96
65	2-1/2"	112	46	185	145	122	4/8-ø18	185	145	122	8-ø18	180	137.7	105	4-ø19	190	149.2	105	8-ø22	145	97
80	3"	114	48	200	160	138	8-ø18	200	160	138	8-ø18	190	152.4	127	4-ø19	210	168.3	127	8-ø22	167	108
100	4"	127	53	220	180	158	8-ø18	235	190	162	8-ø22	230	190.5	157	8-ø19	255	200	157	8-ø22	195	128
125	5"	140	58	250	210	188	8-ø18	270	220	188	8-ø26	255	215.9	186	8-ø22	280	235	186	8-ø22	240	145
150	6"	140	58	285	240	212	8-ø22	300	250	218	8-ø26	280	241.3	216	8-ø22	320	269.9	216	12-ø22	260	168
200	8"	152	67/71	340	295	268	12-ø22	360	310	278	12-ø26	345	298.5	270	8-ø22	380	330.2	270	12-ø26	290	190
250	10"	165	74	405	355	320	12-ø26	425	370	335	12-ø30	405	362	324	12-ø26	445	387.4	324	16-ø29	310	235
300	12"	178	83	460	410	378	16-ø26	485	430	305	16-ø30	485	431.8	381	12-ø26	520	450.8	381	16-ø32	380	266
350	14"	190	92	520	470	438	16-ø26	555	490	450	16-ø33	535	476.3	413	12-ø29	585	514.4	413	20-ø32	435	300
400	16"	216	102	580	525	490	16-ø30	620	550	505	16-ø36	595	539.8	470	16-ø29	650	571.5	470	20-ø35	460	330
450	18"	222	114	640	585	550	20-ø30	670	600	555	20-ø36	635	577.9	533	16-ø32	710	628.6	533	24-ø35	485	355
500	20"	229	127	715	650	610	20-ø33	730	660	615	20-ø36	700	635	584	20-ø32	775	685.8	584	24-ø35	520	385
600	24"	267	154	840	770	725	20-ø36	845	770	720	20-ø39	815	749.3	692	20-ø35	915	812.8	692	24-ø42	610	455
700	28"	292	165	910	840	795	24-ø36	960	875	820	24-ø42	925	863.6	800	28-ø35	1035	939.8	800	28-ø45	675	505