



Type		Length		Connect Platform		Axis		1.6 MPa					2.5 MPa				150LB				300LB				High	
DN	NPS	L	L1	F	K	N-Øm	□	h	D	D1	D2	Z-Ød	D	D1	D2	Z-Ød	D	D1	D2	Z-Ød	D	D1	D2	Z-Ød	H	H1
50	2"	108	43	F05	50	4-Ø8	11*11	12	165	125	102	4-Ø18	165	125	102	4-Ø18	150	120.7	92	4-Ø19	165	127	92	8-Ø19	130	96
65	2-1/2"	112	46	F05	50	4-Ø8	11*11	12	185	145	122	4/8-Ø18	185	145	122	8-Ø18	180	137.7	105	4-Ø19	190	149.2	105	8-Ø22	145	97
80	3"	114	48	F07	70	4-Ø10	14*14	16	200	160	138	8-Ø18	200	160	138	8-Ø18	190	152.4	127	4-Ø19	210	168.3	127	8-Ø22	167	108
100	4"	127	53	F07	70	4-Ø10	14*14	16	220	180	158	8-Ø18	235	190	162	8-Ø22	230	190.5	157	8-Ø19	255	200	157	8-Ø22	195	128
125	5"	140	58	F10	102	4-Ø12	17*17	19	250	210	188	8-Ø18	270	220	188	8-Ø26	255	215.9	186	8-Ø22	280	235	186	8-Ø22	240	145
150	6"	140	58	F10	102	4-Ø12	17*17	21	285	240	212	8-Ø22	300	250	218	8-Ø26	280	241.3	216	8-Ø22	320	269.9	216	12-Ø22	260	168
200	8"	152	67/71	F12	125	4-Ø14	19*19	24	340	295	268	12-Ø22	360	310	278	12-Ø26	345	298.5	270	8-Ø22	380	330.2	270	12-Ø26	290	190
250	10"	165	74	F12	125	4-Ø14	22*22	29	405	355	320	12-Ø26	425	370	335	12-Ø30	405	362	324	12-Ø26	445	387.4	324	16-Ø29	310	235
300	12"	178	83	F14	140	4-Ø18	27*27	29	460	410	378	16-Ø26	485	430	305	16-Ø30	485	431.8	381	12-Ø26	520	450.8	381	16-Ø32	380	266
350	14"	190	92	F14	140	4-Ø18	36*36	38	520	470	438	16-Ø26	555	490	450	16-Ø33	535	476.3	413	12-Ø29	585	514.4	413	20-Ø32	435	300
400	16"	216	102	F14	140	4-Ø18	36*36	38	580	525	490	16-Ø30	620	550	505	16-Ø36	595	539.8	470	16-Ø29	650	571.5	470	20-Ø35	460	330
450	18"	222	114	F16	165	4-Ø22	36*36	38	640	585	550	20-Ø30	670	600	555	20-Ø36	635	577.9	533	16-Ø32	710	628.6	533	24-Ø35	485	355
500	20"	229	127	F16	165	4-Ø22	Ø55	60	715	650	610	20-Ø33	730	660	615	20-Ø36	700	635	584	20-Ø32	775	685.8	584	24-Ø35	520	385
600	24"	267	154	F20	200	8-Ø18	Ø62	80	840	770	725	20-Ø36	845	770	720	20-Ø39	815	749.3	692	20-Ø35	915	812.8	692	24-Ø42	610	455
700	28"	292	165	F25	254	8-Ø18	Ø72	90	910	840	795	24-Ø36	960	875	820	24-Ø42	925	863.6	800	28-Ø35	1035	939.8	800	28-Ø45	675	505